



STATE INTELLECTUAL PROPERTY OFFICE OF THE P.R.C.

[HOME](#)[ABOUT SIPO](#)[NEWS](#)[LAW & POLICY](#)[SPECIAL TOPIC](#)

&gt;&gt;[P

<b>Title:</b> Waveform and frame structure for fixed wireless loop synchronous CDMA communications system			
<b>Application Number:</b>	98812005	<b>Application Date:</b>	1998.11.16
<b>Publication Number:</b>	1281561	<b>Publication Date:</b>	2001.01.24
<b>Approval Pub. Date:</b>		<b>Granted Pub. Date:</b>	
<b>International Classification:</b>	G06F11/10;H04B15/00;H04J3/24;H04K1/00;H04L1/02		
<b>Applicant(s) Name:</b>	L-3 Communications Corp.		
<b>Address:</b>			
<b>Inventor(s) Name:</b>	P. L. Stephenson;T. R. Giallorenzi;J. M. Harris		
<b>Attorney &amp; Agent:</b>	zou guangxin		
<b>Abstract</b>			
<p>Disclosed is a method for transmitting information in a CDMA communication system including (a) multiplexing control information into a data stream; (b) encoding (54) the data stream to form a stream of encoded I/Q symbol pairs; (c) inserting synchronization information into the stream of encoded I/Q symbols pairs; and (d) spreading the encoded pairs and the inserted synchronization information using a same pseudonoise (pn) spreading code (14e) prior to transmission. The preferred frame structure includes an unencoded synchronization field followed by a plurality of multi-byte fields. Individual ones of the plurality of data fields (80A) are separated by a control message field (80B). Individual ones of the data fields contain a single byte of a multi-byte control message frame (82).</p>			

Close

Copyright © 2007 SIPO. All Rights Reserved